

**FFAP-A15Z-TFD-072**

HFC, R-134a, 60Hz, 3-Phase, 460V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.6	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	6.3
Unit Width (in):	18.4	Compressor:	ZS09KAE-TFD-118
Ship Weight (lbs):	123.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	28.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	3.8
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	3MA	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

**Performance**

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS09KAE-TFD-118 x 1	Subcooling (°F):	5
Performance No:	41489	Air Flow Rate (CFM):	1070

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	3,580	96.2	6.2	4.6
0	4,060	97.0	7.0	5.0
5	4,590	97.9	7.9	5.5

10	5,170	98.9	8.9	6.1
15	5,800	99.9	9.9	6.7
20	6,500	101.0	11.0	7.4
25	7,260	102.2	12.2	8.1